











MODEL KP

MARKA / BRAND	
ONAY Approval	UL-300
KAPASİTE Capacity	2,75 Galon (KP-275)
	2,75 Gallon (KP-275)
	3,75 Galon (KP-375)
	3,75 Gallon (KP-375)
	4,75 Galon (KP-475)
	4,75 Gallon (KP-475)
	6,14 Galon (KP-600)
	6,14 Gallon (KP-600)
BASINÇ Pressure	240 Psi (1655 kPa)



SİLİNDİR CYLINDER	MEKANİK TAHLİYE MODÜLÜ MECHANICAL RELEASE MODULE	AZOTLU TETİKLEME SİLİNDİRLERİ NITROGEN ACTUATION CYLINDER	MANUEL BOŞALTIMA İSTASYONU MANUAL PULL STATION	
				
LANYARD ALGILAMA SİSTEMİ LANYARD DETECTION SYSTEM	TİP "K" ERİYEİLİR BAĞLANTI TYPE "K" FUSIBLE LINK	HALKALI ÇIVATA EYEBOLT	KP TAHLİYE NOZULLARI KP DISCHARGE NOZZLES	
				
BOŞALTIMA BAĞLANTI KİTİ KP600 DISCHARGE FITTING KIT KP600	HAVALANDIRMA TAPASI VENT PLUG	KP600 PNÖMATİK AKTÜATÖR KP600 PNEUMATIC ACTUATOR	HIZLI KEÇELİ ADAPTÖR QUICK SEAL ADAPTER	SIKIŞTIRMA KEÇELİ ADAPTÖR COMPRESSION SEAL ADAPTER
