


Adapters

Geberit Mapress adapter with male thread



Application Purpose

- For pipe systems carrying sea water
- Not suitable for drinking water

Characteristics

- Leaky if unpressed
- With pressing indicator
- Male thread

Product Details

Product material	CuNi10Fe1.6Mn, product material no. 2.1972.11
------------------	---


Scope Of Delivery

- Seal ring CIIR black

Ordering Information

Article no.	dØ [mm]	R ["]	H [cm]	L [cm]
68703	15	1/2	3,3	5,3
68715	22	1/2	3,3	5,4
68707	22	3/4	3,7	5,8
68708	28	1	4,1	6,4
68709	35	1 1/4	4,6	7,2
68710	42	1 1/2	4,7	7,7
68711	54	2	5,4	8,9

Geberit Mapress adapter with male thread NPT



Application Purpose

- For pipe systems carrying sea water
- Not suitable for drinking water

Characteristics

- With pressing indicator
- Leaky if unpressed
- Sea water resistant
- Male thread NPT

Product Details

Product material	CuNi10Fe1.6Mn, product material no. 2.1972.11
------------------	---


Scope Of Delivery

- Seal ring CIIR black

Ordering Information

Article no.	dØ [mm]	R ["]	H [cm]	L [cm]
68833	15	1/2 NPT	4,1	6,1
68837	22	3/4 NPT	4,2	6,3
68838	28	1 NPT	4,9	7,2
68839	35	1 1/4 NPT	5,2	7,8
68840	42	1 1/2 NPT	5,3	8,3
68841	54	2 NPT	5,5	9

Geberit Mapress adapter with female thread



Application Purpose

- For pipe systems carrying sea water
- Not suitable for drinking water

Characteristics

- Leaky if unpressed
- With pressing indicator
- Female thread

Product Details

Product material	CuNi10Fe1.6Mn, product material no. 2.1972.11
------------------	---


Scope Of Delivery

- Seal ring CIIR black

Ordering Information

Article no.	dØ [mm]	Rp ["]	L [cm]	Z [cm]
67802	15	1/2	5,5	2,2
67805	22	1/2	5,6	2,2
67806	22	3/4	5,8	2,2
67809	28	1	6,4	2,4
67811	35	1 1/4	7	2,5
67814	42	1 1/2	7,4	2,5
67818	54	2	8,9	3,1

Geberit Mapress adapter union with male thread



Application Purpose

- For pipe systems carrying sea water
- Not suitable for drinking water

Characteristics

- Leaky if unpressed
- With pressing indicator
- Male thread
- Removable, flat seal

Product Details

Product material	CuNi10Fe1.6Mn, product material no. 2.1972.11
------------------	---

Operating temperature with EPDM flat gasket	0-100 °C
---	----------

Scope Of Delivery

- Seal ring CIIR black
- EPDM flat gasket

Ordering Information

Article no.	dØ [mm]	R ["]	G ["]	H [cm]	L [cm]
67232	15	1/2	3/4	6,1	8,1
67234	22	1/2	1	6,3	8,4
67243	22	3/4	1	6,4	8,5
67235	28	1	1 1/4	7,3	9,6
67236	35	1 1/4	1 1/2	7,8	10,4
67237	42	1 1/2	1 3/4	7,9	10,9
67238	54	2	2 3/8	8,9	12,4