



VIZA.EX26617 Fittings, Grooved and Plain End

Page Bottom

Fittings, Grooved and Plain End

See General Information for Fittings, Grooved and Plain End

SHANDONG DINGLIANG FIRE TECHNOLOGY CO LTD

EX26617

Cheliuzhuang Village Jiulong Sub-office Fangzi District
Weifang, Shandong 261200 CHINA

The following fittings are intended for use with SHANDONG DINGLIANG FIRE TECHNOLOGY CO LTD's (EX26616) listed rubber gasketed fittings.

Grooved end

Model	Type	Size In.	Rated Pressure (psig)
XGQT01	90 degree elbow	1, 1-1/4, 1-1/2, 2, 2-1/2, 3 OD (76.1 mm), 3, 4; 5-1/2 OD (139.7 mm), 5, 6-1/2 OD (165.1 mm), 6, 8, 10, 12	300
XGQT01L	Long Radius 90°Elbow	1, 1-1/4, 1-1/2, 2, 2-1/2, 3OD(76.1mm), 3, 4, 5-1/2OD(139.7mm), 5, 6-1/2OD(165.1mm), 6, 8, 10, 12	300
XGQT01S	90° End-All Elbow (Reducing, Grooved x Threaded)	1-1/4 x 1/2, 3/4, 1; 1-1/2 x 1/2, 3/4, 1; 2 x 1/2, 3/4, 1; 3OD(76.1mm) x 1/2, 3/4, 1; 3 x 3OD(76.1mm); 4 x 2, 3OD(76.1mm), 3	300
XGQT01G	90° Reducing Elbow (Grooved x Grooved)	6-1/2OD(165.1mm) x 4; 6 x 4	300
XGQT02	45 degree elbow	1, 1-1/4, 1-1/2, 2, 2-1/2, 3 OD (76.1 mm), 3, 4; 5-1/2 OD (139.7 mm), 5, 6-1/2 OD (165.1 mm), 6, 8, 10, 12	300
XGQT07	22.5 degree elbow	1, 1-1/4, 1-1/2, 2, 2-1/2, 3 OD (76.1 mm), 3, 4; 5-1/2 OD (139.7 mm), 5, 6-1/2 OD (165.1 mm), 6, 8	300
XGQT08	11.25 degree elbow	1, 1-1/4, 1-1/2, 2, 2-1/2, 3 OD (76.1 mm), 3, 4; 5-1/2 OD (139.7 mm), 5, 6-1/2 OD (165.1 mm), 6, 8	300
XGQT03	Equal tee	1, 1-1/4, 1-1/2, 2, 2-1/2, 3 OD (76.1 mm), 3, 4; 5-1/2 OD (139.7 mm), 5, 6-1/2 OD (165.1 mm), 6, 8, 10, 12	300
XGQT03L	Long Equal Tee	1, 1-1/4, 1-1/2, 2, 2-1/2, 3OD(76.1mm), 3, 4, 5-1/2OD(139.7mm), 5, 6-1/2OD(165.1mm), 6, 8, 10, 12	300
XGQT04	Grooved reducing tee	2 x 1, 1-1/4, 1-1/2; 2-1/2 x 1, 1-1/4, 1-1/2, 2; 3 OD (76.1 mm) x 1, 1-1/4, 1-1/2, 2; 3 x 1, 1-1/4, 1-1/2, 2, 2-1/2, 3 OD (76.1 mm); 4 x 1, 1-1/4, 1-1/2, 2, 2-1/2, 3 OD (76.1 mm), 3; 5-1/2 OD (139.7 mm) x 2, 2-1/2, 3 OD (76.1 mm), 3, 4; 6-1/2 OD (165.1 mm) x 2, 2-1/2, 3 OD (76.1 mm), 3, 4, 5-1/2 OD (139.7 mm); 6 x 2, 2-1/2, 3 OD (76.1 mm), 3, 4; 5-1/2 OD (139.7 mm); 8 x 2, 2-1/2, 3 OD (76.1 mm), 3, 4; 6-1/2 OD (165.1 mm), 6; 10 x 6-1/2 OD (165.1 mm), 6, 8; 12 x 6-1/2 OD (165.1 mm), 6, 10	300
XGQT04S	Threaded reducing tee	2 x 1, 1-1/4, 1-1/2; 2-1/2 x 1, 1-1/4, 1-1/2, 2; 3 OD (76.1 mm) x 1, 1-1/4, 1-1/2, 2; 3 x 1, 1-1/4, 1-1/2, 2, 3 OD (76.1 mm); 4 x 1, 1-1/4, 1-1/2, 2, 3 OD (76.1 mm), 3; 5-1/2 OD (139.7 mm) x 1, 1-1/4, 1-1/2, 2, 3 OD (76.1 mm), 3, 4; 6-1/2 OD (165.1 mm) x 1, 1-1/4, 1-1/2, 2, 3 OD (76.1 mm), 3, 4; 6 x 1, 1-1/4, 1-1/2, 2, 3 OD (76.1 mm), 3, 4	300
XGQT05	Equal cross	1-1/4, 1-1/2, 2, 2-1/2, 3 OD (76.1 mm), 3, 4; 5-1/2 OD (139.7 mm), 5, 6-1/2 OD (165.1 mm), 6, 8, 10, 12	300
XGQT05L	Long Equal Cross	1, 1-1/4, 1-1/2, 2, 2-1/2, 3OD(76.1mm), 3, 4, 5-1/2OD(139.7mm), 5, 6-1/2OD(165.1mm), 6, 8, 10, 12	300

XGQT09	Grooved reducing cross	3 x 2; 4 x 2, 2-1/2, 3 OD (76.1 mm), 3; 5-1/2 OD (139.7 mm) x 2, 2-1/2, 3 OD (76.1 mm), 3, 4; 6-1/2 OD (165.1 mm) x 2, 2-1/2, 3 OD (76.1 mm), 3, 4; 6 x 2, 2-1/2, 3 OD (76.1 mm), 3, 4; 8 x 2, 2-1/2, 3 OD (76.1 mm), 3, 4; 6-1/2 OD (165.1 mm), 6	300
XGQT05S	Threaded reducing cross	3 OD (76.1 mm) x 2; 3 x 2, 3 OD (76.1 mm); 4 x 1, 1-1/4, 1-1/2, 2, 3 OD (76.1 mm), 3; 5-1/2 OD (139.7 mm) x 3 OD (76.1 mm), 3; 6-1/2 OD (165.1 mm) x 1, 1-1/4, 1-1/2, 2, 3 OD (76.1 mm), 3, 4; 8 x 3 OD (76.1 mm), 3	300
XGQT06	End cap	1, 1-1/4, 1-1/2, 2, 2-1/2, 3 OD (76.1 mm), 3, 4; 5-1/2 OD (139.7 mm), 5, 6-1/2 OD (165.1 mm), 6, 8, 10, 12	300
XGQT06S	Concentric End Cap With Hole	2, 2-1/2, 3OD(76.1mm), 3, 4, 5-1/2OD(139.7mm), 5, 6-1/2OD(165.1mm), 6, 8 10, 12	300
XGQT06P	Eccentric End Cap With Hole	2, 2-1/2, 3OD(76.1mm), 3, 4, 5-1/2OD(139.7mm), 5, 6-1/2OD(165.1mm), 6, 8 10, 12	300
XGQT07G	Grooved concentric reducer	1-1/4 x 1; 1-1/2 x 1, 1-1/4; 2 x 1, 1-1/4, 1-1/2; 2-1/2 x 1, 1-1/4, 1-1/2, 2; 3 OD (76.1 mm) x 1, 1-1/4, 1-1/2, 2; 3 x 1, 1-1/4, 1-1/2, 2, 2-1/2; 4 x 1, 1-1/4, 1-1/2, 2, 2-1/2, 3; 5-1/2 OD (139.7 mm) x 2, 2-1/2, 3 OD (76.1 mm), 3, 4; 6-1/2 OD (165.1 mm) x 2, 2-1/2, 3 OD (76.1 mm), 3, 4; 5-1/2 OD (139.7 mm); 6 x 2, 2-1/2, 3 OD (76.1 mm), 3, 4, 5-1/2 OD (139.7 mm); 8 x 2, 2-1/2, 3 OD (76.1 mm), 3, 4; 5-1/2 OD (139.7 mm), 6-1/2 OD (165.1 mm), 6	300
XGQT07P	Grooved eccentric reducer	3 x 2; 4 x 2, 2-1/2, 3 OD (76.1 mm), 3; 5-1/2 OD (139.7 mm) x 2, 2-1/2, 3 OD (76.1 mm), 3, 4; 6-1/2 OD (165.1 mm) x 2, 2-1/2, 3, 4; 6 x 2, 2-1/2, 3 OD (76.1 mm), 3, 4; 8 x 2, 2-1/2, 3 OD (76.1 mm), 3, 6-1/2 OD (165.1 mm), 6; 10 x 8	300
XGQT07S	Threaded concentric reducer	1-1/4 x 1; 1-1/2 x 1, 1-1/4; 2 x 1/2, 1, 1-1/4, 1-1/2; 2-1/2 x 1-1/4, 1-1/2, 2; 3 OD (76.1 mm) x 1, 1-1/4, 1-1/2, 2; 3 x 1/2, 1, 1-1/4, 1-1/2, 2, 3 OD (76.1 mm); 4 x 1, 1-1/4, 1-1/2, 2, 3 OD (76.1 mm), 3; 5-1/2 OD (139.7 mm) x 3, 4; 6-1/2 OD (165.1 mm) x 1, 2, 3 OD (76.1 mm), 3, 4; 6 x 1, 2, 2-1/2, 3 OD (76.1 mm), 4; 8 x 3 OD (76.1 mm), 3, 4	300
XGQT10	Flange adapter	2, 2-1/2, 3 OD (76.1 mm), 3, 4; 5-1/2 OD (139.7 mm), 6-1/2 OD (165.1 mm), 6, 8, 10, 12	300
XGQT10A	Class 150 Flange Adapter	2, 2-1/2, 3OD(76.1mm), 3, 4, 5-1/2OD(139.7mm), 5, 6-1/2OD(165.1mm), 6, 8, 10, 12;	300



Trademark and/or Tradename:

Last Updated on 2016-07-06

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".