


Geberit Mapress adapter union with male thread and plain end



Application Purpose

- For sanitary and industrial applications
- For heating installations

Characteristics

- Male thread
- Removable, flat seal
- Plain end

Product Details

Product material	CrNiMo steel 1.4401 (DIN EN 10088)
Operating temperature with EPDM flat gasket	0–100 °C


Scope Of Delivery

- EPDM flat gasket

Ordering Information

Article no.	dØ [mm]	R ["]	G ["]	H [cm]
35400	15	1/2	3/4	8,6
35402	18	1/2	3/4	8,6
35405	22	3/4	1	9,2
35407	28	1	1 1/4	10,1
35408	35	1 1/4	1 1/2	10,9
35409	42	1 1/2	1 3/4	11,5
35410	54	2	2 3/8	12,9

Geberit Mapress adapter union with female thread



Application Purpose

- For sanitary and industrial applications
- For heating installations

Characteristics

- Female thread
- Removable, flat seal
- Union nut made of brass
- Leaky if unpressed
- With pressing indicator

Product Details

Product material	CrNiMo steel 1.4401 (DIN EN 10088)
Operating temperature with EPDM flat gasket	0–100 °C


Scope Of Delivery

- Seal ring CIIR black
- EPDM flat gasket

Ordering Information

Article no.	dØ [mm]	Rp ["]	G ["]	L [cm]	Z [cm]
35300	15	1/2	3/4	5,9	2,6
35301	15	3/4	3/4	6,1	2,6
35302	18	1/2	3/4	5,9	2,6
35303	18	3/4	3/4	6,1	2,6
35304	22	3/4	1	6,3	2,7
35305	22	1	1	6,6	2,8
35306	28	1	1 1/4	7,1	3,1
35307	35	1 1/4	1 1/2	7,7	3,2
35308	42	1 1/2	1 3/4	8,2	3,3
35309	54	2	2 3/8	9,5	3,7

Geberit Mapress adapter union with female thread, union nut made of stainless steel



Application Purpose

- For sanitary and industrial applications
- For heating installations

Characteristics

- Female thread
- Removable, flat seal
- Union nut made of CrNi steel
- Leaky if unpressed
- With pressing indicator

Product Details

Product material	CrNiMo steel 1.4401 (DIN EN 10088)
Operating temperature with EPDM flat gasket	0–100 °C

Scope Of Delivery

- Seal ring CIIR black
- EPDM flat gasket

Ordering Information

Article no.	dØ [mm]	Rp ["]	G ["]	L [cm]	Z [cm]
35350	15	1/2	3/4	5,9	2,6
35357	15	3/4	3/4	6,1	2,6
35351	18	1/2	3/4	5,9	2,6
35358	18	3/4	3/4	6,1	2,6
35352	22	3/4	1	6,3	2,7
35359	22	1	1	6,6	2,8
35353	28	1	1 1/4	7,1	3,1
35354	35	1 1/4	1 1/2	7,7	3,2
35355	42	1 1/2	1 3/4	8,2	3,3
35356	54	2	2 3/8	9,5	3,7