

Cap

No. 60




No. 60



No. 60

Size		No. 60 Cap	
Nominal Size	Actual Outside Diameter	"T" Thickness	Approx. Weight Each
inches mm	inches mm	inches mm	lbs. kg
3/4	1.050	0.88	0.2
20	26.9	22	0.1
1	1.315	0.88	0.3
25	33.7	22	0.1
1 1/4	1.660	0.88	0.3
32	42.4	22	0.1
1 1/2	1.900	0.88	0.5
40	48.3	22	0.2
2	2.375	0.88	0.6
50	60.3	22	0.3
2 1/2	2.875	0.88	1.0
65	73.0	22	0.5
76.1 mm	3.000 76.1	0.88 22	1.2 0.5
3	3.500	0.88	1.2
80	88.9	22	0.5
3 1/2	4.000	0.88	2.5
90	101.6	22	1.1
108.0 mm	4.250 108.0	1.00 25	2.3 1.0
4	4.500	1.00	2.5
100	114.3	25	1.1
133.0 mm	5.250 133.0	1.00 25	4.5 2.0
139.7 mm	5.500 139.7	1.00 25	4.5 2.0
5	5.563	1.00	4.6
125	141.3	25	2.1

13 For 14"/350 mm and larger roll grooved systems, Victaulic offers the Advanced Groove System (AGS). For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

Size		No. 60 Cap	
Nominal Size	Actual Outside Diameter	"T" Thickness	Approx. Weight Each
inches mm	inches mm	inches mm	lbs. kg
159.0 mm	6.250 159.0	1.00 25	6.8 3.1
165.1 mm	6.500 165.1	1.00 25	7.3 3.3
6 150	6.625 168.3	1.00 25	6.1 2.8
8 200	8.625 219.1	1.19 30	13.1 5.9
10 250	10.750 273.0	1.25 32	21.0 9.5
12 300	12.750 323.9	1.25 32	35.6 16.2
14 ¹³ 350	14.000 355.6	9.50 (s) 241	+
16 ¹³ 400	16.000 406.4	10.00 (s) 254	+
18 ¹³ 450	18.000 457.0	11.00 (s) 279	+
20 ¹³ 500	20.000 508.0	12.00 (s) 305	+
24 ¹³ 600	24.000 610.0	13.50 (s) 343	+
14 – 60 350 – 1500	For AGS fitting information, see publication 20.05 		

13 For 14"/350 mm and larger roll grooved systems, Victaulic offers the Advanced Groove System (AGS). For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

General Notes

No. 60 cap is not suitable for use in vacuum service with Style 72 or 750 couplings. No. 61 bull plugs should be used.

Note: All fittings are ductile iron unless otherwise noted with an (sw) or (s).

(s) = Carbon Steel Direct Roll Groove (OGS)

(sw) = Carbon Steel Segmentally Welded

+ Contact Victaulic for details.