


STYLE 06 LONG RADIUS

Dirsek 90° / Elbow 90°

Maximum working pressure: 34.5 bar




Nominal Size (Inches / DN)	Pipe Outside Diameter	Dimen- sion A	Weight Kg.	Approvals
1" / 25	33.7	-	-	-
1¼" / 32	42.4	64.0	0.45	FM / UL VDS
1½" / 40	48.3	-	-	-
2" / 50	60.3	82.5	0.71	FM / UL LPCB / VDS
2½" / 65	76.1	95.0	1.36	FM / UL LPCB / VDS
3" / 80	88.9	108.0	1.70	FM / UL LPCB / VDS
4" OD	108.0	127.0	2.60	FM / UL VDS
4" / 100	114.3	127.0	2.70	FM / UL
5" OD	133.0	140.0	3.27	VDS
5" / 125	139.7	140.0	4.30	UL / LPCB VDS
6" OD	159.0	-	-	-
6" OD	165.1	165.0	6.00	UL / LPCB
6" / 150	168.3	165.0	5.82	FM / UL LPCB / VDS
8" / 200	219.1	196.0	10.60	FM / UL LPCB / VDS
10" / 250	273.0	229.0	26.60	FM / UL VDS
12" / 300	323.9	254.0	37.00	UL
14" / 350	355.6	282.0	45.50	-
16" / 400	406.4	305.0	80.00	-

STYLE 66 SHORT RADIUS

Dirsek 90° / Elbow 90°

Maximum working pressure: 34.5 bar



Nominal Size (Inches / DN)	Pipe Outside Diameter	Dimen- sion A	Weight Kg.	Approvals
1" / 25	33.7	58.0	0.26	LPCB / VDS
1¼" / 32	42.4	70.0	0.42	FM / LPCB VDS
1½" / 40	48.3	70.0	0.51	FM / LPCB
2" / 50	60.3	70.0	0.59	FM / UL LPCB / VDS
2½" / 65	76.1	76.0	0.91	FM / UL LPCB / VDS
3" / 80	88.9	85.5	1.25	FM / UL LPCB / VDS
4" OD	108.0	101.0	2.60	VDS
4" / 100	114.3	101.0	2.18	FM / UL
5" OD	133.0	-	-	-
5" / 125	139.7	124.0	4.0	FM / UL LPCB / VDS
6" OD	159.0	140.0	5.70	VDS
6" OD	165.1	140.0	5.2	FM / UL LPCB / VDS
6" / 150	168.3	140.0	5.13	FM / UL LPCB / VDS
8" / 200	219.1	174.0	8.3	FM / UL LPCB / VDS
10" / 250	273.0	-	-	-
12" / 300	323.9	-	-	-
14" / 350	355.6	-	-	-
16" / 400	406.4	-	-	-