


STYLE 64 SHORT RADIUS

Dirsek 45° / Elbow 45°

Maximum working pressure: 34.5 bar




Nominal Size (Inches / DN)	Pipe Outside Diameter	Dimen- sion A	Weight Kg.	Approvals
1" / 25	33.7	-	-	-
1¼" / 32	42.4	44.5	0.30	FM / UL LPCB / VDS
1½" / 40	48.3	44.5	0.36	FM / UL
2" / 50	60.3	51.0	0.51	FM / UL LPCB / VDS
2½" / 65	76.1	57.0	0.86	FM / UL LPCB / VDS
3" / 80	88.9	63.5	1.16	FM / UL LPCB / VDS
4" OD	108.0	76.0	1.65	VDS
4" / 100	114.3	76.0	1.85	FM / UL
5" OD	133.0	82.5	2.77	-
5" / 125	139.7	82.2	3.12	FM / UL LPCB / VDS
6" OD	159.0	90.0	3.76	VDS
6" OD	165.1	89.0	4.10	FM / UL LPCB
6" / 150	168.3	89.0	3.90	FM / UL LPCB / VDS
8" / 200	219.1	108.0	7.60	FM / UL VDS
10" / 250	273.0	120.0	16.65	FM / UL VDS
12" / 300	323.9	133.0	23.50	FM / UL VDS
14" / 350	355.6	-	-	-
16" / 400	406.4	-	-	-

STYLE 04 LONG RADIUS

Dirsek 45° / Elbow 45°

Maximum working pressure: 34.5 bar



Nominal Size (Inches / DN)	Pipe Outside Diameter	Dimen- sion A	Weight Kg.	Approvals
1" / 25	33.7	-	-	-
1¼" / 32	42.4	44.5	0.38	UL / VDS
1½" / 40	48.3	44.5	0.45	FM / UL / VDS
2" / 50	60.3	51.0	0.64	FM / UL / VDS
2½" / 65	76.1	57.0	1.00	FM / UL / VDS
3" / 80	88.9	63.5	1.50	FM / UL / VDS
4" OD	108.0	-	-	-
4" / 100	114.3	76.0	2.55	FM / UL / VDS
5" OD	133.0	82.5	3.50	-
5" / 125	139.7	82.2	3.80	VDS
6" OD	159.0	11.9	5.40	VDS
6" OD	165.1	89.0	5.60	UL
6" / 150	168.3	89.0	5.70	FM / UL / VDS
8" / 200	219.1	108.0	11.20	FM / UL / VDS
10" / 250	273.0	120.0	15.00	VDS
12" / 300	323.9	-	-	-
14" / 350	355.6	-	-	-
16" / 400	406.4	-	-	-